

TitanBac® Plus Backing

The problems that can arise when carpet is exposed to moisture are well documented: mold and mildew, odor, product deterioration and total installation failure. However, specifying and installing the right backing, such as J+J Flooring TitanBac Plus, can effectively prevent typical moisture problems. TitanBac Plus also improves carpet performance by allowing it to be more vigorously cleaned to retain its aesthetic appeal for a longer period of time.

Features and Benefits

- Contains pre-consumer and post-consumer recycled content and contributes to LEED
- Recyclable through the J+J Flooring Carpet Reclamation Program
- Electricity and natural gas used in manufacturing is offset with renewable energy
- Prevents moisture from penetrating into the subfloor, easier spill clean-up, reduces odor
- EPD and HPD Available

Lifetime Broadloom Performance Warranties

- Protection from delamination failure
- Tuft bind strength (edge ravel, yarn pulls and zippering)
- Moisture barrier

Testing and Specifications

- Average Backing Thickness: .156 inch (approximate)
- Backing Weight: 36-45 oz./sy
- Recycled Content: 25-30% (pre and post-consumer)
- Standard Size: 12 feet wide
- CRI Green Label Plus™ Certified
- NSF/ANSI 140 Gold Certified
- Class 1 (ASTM E 648 Radiant Panel)
- Less than 450 (ASTM E662 NBS Smoke)
- Moisture Barrier - Passes British Spill Test (24 hours)
- Required Adhesive and Seam Sealer: Commercialon® Premium Carpet Adhesive and Commercialon® Seam Sealer

More Options

For more information, please contact your J+J Flooring Sales Representative or call 800 241 4586 x8020.

