



Kinetex[®] Adhesive

Warranties

Kinetex[®] Adhesive is warranted against product failure for the lifetime of the installation of Kinetex modular textile flooring.

We warrant that Kinetex Adhesive will bond the modular textile flooring to the properly prepared substrate for the life of the installation. This warranty is contingent upon strict adherence to proper adhesive transfer and spread rates, and substrates conforming to specified porosity, moisture¹ and alkalinity² thresholds.

In the event our Kinetex Adhesive fails to perform to specified standards, we must be notified in writing within 15 calendar days of indication of failure. Included with that notification must be a copy of the invoice for the Kinetex Adhesive. Approved personnel will then inspect the installation.

Should it be determined from the inspection that our Kinetex Adhesive failed to perform as warranted above, we will resolve the deficiency at its discretion by one or more of the following methods at no charge for materials, freight, and labor:

A) refund the full purchase price of the Kinetex product in the affected area, **B)** repair the affected area, or **C)** replace the affected area. Areas must be cleared at the customer's expense of all equipment, furnishings, partitions, and similar materials that may have been placed over the Kinetex subsequent to completion of the original installation. We are not responsible for damages caused by the improper use of this adhesive or failure to comply with the instructions accompanying this product.

Exclusion

This warranty is assigned to the original purchaser for the Kinetex textile composite flooring installed in its original location, and this warranty is non-transferable. Flooding voids all warranties.

- 1) Maximum RH of concrete 100%. No RH testing is required. No standing water or condensation can be present during time of install. Subfloor temperature must be at least 65°F.
- 2) Maximum pH reading is 11.0 using pH testing strips.